

### Low PIM Ceiling Mount Omnidirectional Antenna

#### LOW PIM MULTI-BAND CEILING MOUNTED OMNIDIRECTIONAL ANTENNA

The CMS38606P is an indoor broadband low PIM omnidirectional ceiling mount antenna. It is designed to provide pattern coverage that is optimized for indoor requirements at 380-520 MHz, 600- 960 MHz, 1395-1435 MHz and 1690-6000 MHz frequency bands. The antenna features a pattern that has been specifically shaped to provide optimal performance from a ceiling mount location.



Patent Pending  
CMS38606P-30NF

#### FEATURES

- Low Profile aesthetically neutral housing
- Mounts directly and easily to ceiling tile
- Performance optimized using Laird proprietary RF optimization tools
- Excellent flame retardancy rating
- IP67 rated ingress protection and RoHS compliant
- Broadband product with provision for the UHF, 600 MHz, 1390-1432 MHz and AWS-3 bands in a single solution.

#### MARKETS

- Public Safety DAS
- In-Building wireless
- Neutral host providers
- Cellular & LTE
- Small cells

#### BENEFITS

- Low PIM performance minimizes interference and improves in-building wireless network coverage and capacity.
- Attractive, compact design and form factor ideal for indoor solution applications.
- Compliant with in-building International Fire Code (IFC) & National Fire Protection Association (NFPA) regulations.

PARAMETER	SPECIFICATIONS						
Frequency Bands, MHz	380-520	600-806	806-960	1395-1435	1690-2200	2200-4300	4300-6000
Peak Gain, dBi (Typ)	2.2	2.1	2.6	5.3	5.7	5.8	5.4
Peak Gain, dBi (Max)	3.1	2.7	2.9	5.4	6.1	7.0	6.1
VSWR (Typ)	<2.8:1	<1.7:1	<1.9:1	<1.4:1	<1.6:1	<1.9:1	<1.6:1
VSWR (Max)	<3.0:1	<2.0:1	<2.0:1	<2.0:1	<2.0:1	<2.0:1	<2.0:1
PIM, 3rd Order, 2 x 20W (Typ)	<-154 dBc	<-154 dBc		NA		<-152 dBc	
PIM, 3rd Order, 2 x 20W (Max)	<-150 dBc	<-150 dBc		NA		<-150 dBc	
Nominal Impedance	50 Ω						
Polarization	Vertical						
Azimuth Beam Width	360°, Omnidirectional						
Max Power (Ambient 25°C/77°F)	50 Watts						
Cable Length/Connector	30 cm (12") Type N-female						
Antenna Dimension (Ht x Dia)	133 x 298 mm (5.23" x 11.7")						
Weight	0.8 kg (1.76 lbs)						
Antenna Color	White						
Radome	PC, UV Stable, UL94-V0 Material						
Operating Temperature (°C)	-30° C to +70° C						
Storage Temperature (°C)	-40° C to +85° C						
Ingress Protection	IP67						
RoHS Compliance	Yes						

Americas: +1.847.839.6907  
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941  
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127  
IAS-AsiaSales@lairdtech.com

[www.lairdtech.com](http://www.lairdtech.com)

Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective by reason of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.





# CMS38606P

## 380 to 960 MHz/1395 to 6000 MHz



### Low PIM Ceiling Mount Omnidirectional Antenna

#### RADIATION PATTERNS



400 MHz





520 MHz





600 MHz





698 MHz



850 MHz





960 MHz





**RADIATION PATTERNS**



**1395 MHz**





**1690 MHz**





**2700 MHz**



**4300 MHz**



**5950 MHz**



ANT-DS-CMS38606P 0715

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.