



Part Number: 8918

Hook-Up/Lead Wire UL AWM Style 1015, (1) 18 AWG (16x30) TC, PVC, 600V, 105° C

Request Sample
Requ

Product Description

One 18 AWG stranded (16x30) tinned copper conductor, PVC insulation.

Technical Specifications

Physical Characteristics (Overall)

| Conduc | Conductor | | | |
|--------|--------------------|-------------|----------|-------------------|
| AWG | Stranding | Mater | rial | No. of Conductors |
| 18 | 16x30 | TC - Tinned | d Copper | 1 |
| Condu | Conductor Count: 1 | | | |
| Condu | Conductor Size: | | 18 AWG | |

Insulation

| Material | Nominal Diameter | Nominal Wall Thickness | Min. Average Wall Thickness |
|--------------------------|------------------|------------------------|-----------------------------|
| PVC - Polyvinyl Chloride | 0.11 in | .0325 in | 0.03 in |

Outer Jacket Material

| Material | Nominal Diameter |
|-----------|------------------|
| No Jacket | 0.11 in |

Electrical Characteristics

Conductor DCR



Current

| Element | Max. Recommended Current [A] |
|--|--|
| Single conductor in free air @ 30C ambient | Single conductor in free air @ 30C ambient 20 amps |

Voltage



Temperature Range

| III. Tanan Batinan | 40500 |
|--------------------|-------|
| UL Temp Rating: | 105°C |
| | |

Mechanical Characteristics

Standards

| NEC/(UL) Specification: | MTW |
|-------------------------|------------------|
| UL AWM Style: | 1015, 1230 |
| CSA Rating: | 600 V, 105°C |
| CSA AWM Specification: | AWM I A/B |
| CSA Type: | AWM I A/B or TEW |

Military Specification: N/A

Applicable Environmental and Other Programs

| EU Directive 2000/53/EC (ELV): | Yes |
|---------------------------------------|-------------------------------|
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-07-01 |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Flammability, LS0H, Toxicity Testing

| UL Flammability: | VW-1 |
|--------------------|-----------|
| CSA Flammability: | FT1 |
| UL voltage rating: | 600 V RMS |

Plenum/Non-Plenum

| No | |
|----|--|
|----|--|

Part Number

Variants

| Item # | Color | Footnote |
|--------------|----------------------|----------|
| 8918 010100 | Black | |
| 8918 0101000 | Black | Р |
| 8918 0105000 | Black | С |
| 8918 013100 | Blue, Dark | |
| 8918 0131000 | Blue, Dark | Р |
| 8918 0135000 | Blue, Dark | С |
| 8918 001100 | Brown | |
| 8918 0011000 | Brown | Р |
| 8918 0081000 | Gray | Р |
| 8918 0085000 | Gray | Р |
| 8918 005100 | Green, Dark | |
| 8918 0051000 | Green, Dark | Р |
| 8918 0055000 | Green, Dark | Р |
| 8918 189100 | Green, Yellow Stripe | A |
| 8918 1891000 | Green, Yellow Stripe | Α |
| 8918 003100 | Orange | |
| 8918 0031000 | Orange | Р |
| 8918 002100 | Red | |
| 8918 0021000 | Red | Р |
| 8918 0025000 | Red | С |
| 8918 0071000 | Violet | Р |
| 8918 009100 | White | |
| 8918 0091000 | White | Р |
| 8918 0095000 | White | С |
| 8918 004100 | Yellow | |
| 8918 0041000 | Yellow | Р |
| 8918 0045000 | Yellow | С |
| Footpote: | C (| DATE DEE |

| Footnote: | C - CRATE REEL PUT-UP. |
|-----------|---|
| Footnote: | P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'. |
| Footnote: | A - STOCKED STRIPE COLORS. |

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.